



ITI LIMITED
(A Government of India Undertaking)

GOVERNMENT OF INDIA

ITI LIMITED CIVIL DEPARTMENT

BANGALORE PLANT

DOORVANI NAGAR BANGALORE 560016

Civil Works for chain link fencing and fixing of Fiber sheet in ITI Main Guest House

ENQUIRY NO / DATE:		ITI/CE/NIT/30/2022-23 / 18.11.2022	DUE DATE:	03.12.2022 @ 12pm	QUOTATION REFERENCE / DATE	
NAME OF THE SUPPLIER						
FULL ADDRESS :						
TEL NO. & MOBILE NO:						
e-MAIL ID :						
GST #:						
MSME UDYAM REGISTRATION REFERENCE:						
Sl. no.	Item Description	Qty	Unit	Rate	Amount inclusive of all Taxes	Remarks
1	Earth work in excavation by mechanical means (Hydraulic excavator)/manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and lift upto 1.5 m, as directed by Engineer-in-charge. All kinds of soil.	2.88	cum		-	
2	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level : 1:3:6 (1 Cement : 3 coarse sand (zone-III) : 6 graded stone aggregate 20 mm nominal size	2.88	cum		-	
3	Steel work welded in built up sections/ framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer using structural steel etc. as required. In gratings, frames, guard bar, ladder, railings, brackets, gates and similar works	798.21	kg		-	
4	Providing and fixing G.I. chain link fabric fencing of required width in mesh size 50x50 mm including strengthening with 2 mm dia wire or nuts, bolts and washers as required complete as per the direction of Engineer-in-charge. Made of G.I. wire of dia 4 mm	110.00	sqm		-	
5	Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade :Two or more coats on new / old work over an under coat of suitable shade with ordinary paint of approved brand and manufacture	270.00	sqm		-	
6	Providing & fixing UV stabilised fiberglass reinforced plastic sheet roofing up to any pitch, including fixing with polymer coated 'J' or 'L' hooks, bolts & nuts 8mm dia. G.I plain/bitumen washers complete but excluding the cost of purlins, rafters, trusses etc. The sheets shall be manufactured out of 2400 TEX panel roving incorporating minimum 0.3% ultra-violet stabiliser in resin system under approximately 2400 psi and hot cured. They shall be of uniform pigmentation and thickness without air pockets and shall conform to IS 10192 and IS 12866.The sheets shall be opaque or translucent, clear or pigmented, textured or smooth as specified. 2 mm thick flat	190.00	sqm		-	
TOTAL (Inclusive of All Taxes)					0.00	