

GOVERNMENT OF INDIA

ITI LIMITED CIVIL DEPARTMENT

BANGALORE PLANT DOORVANI NAGAR BANGALORE 560016

CIVIL WORKS FOR RECONSTRUCTION OF COMPOUND WALL AT A AREA, ITI LIMITED BANGALORE

FNOURY NO / DAIF:		ITI/CE/NIT/23/2022-23 / 29.10.2022	DUE DATE:	12.11.2022 @ 12pm	QUOTATION REFERENCE / DATE	
NAME OF THE SUPPLIER						
FULL ADDRESS :						
TEL NO. & MOBILE NO:						
e-MAIL ID :						
GST #:						
MSME UDYAM REGISTRATION REFERENCE:						
Sl. no.	Item Description	Qty	Unit	Rate	Amount inclusive of all Taxes	Remarks
1	Brick work with common burnt clay F.P.S. (non modular) bricks of class designation 7.5 in superstructure above plinth level up to floor V level in all shapes and sizes in : Cement mortar 1:4 (1 cement : 4 coarse sand)	24.99	cum		-	
2	CEMENT PLASTER (IN FINE SAND) Providing 15 mm cement plaster of mix :1:6 (1 cement: 6 fine sand)	193.20	sqm		-	
3	Earth work in excavation by mechanical means (Hydraulic excavator)/manual means over areas (exceeding 30 cm in depth, 1.5 m in width as well as 10 sqm on plan) including getting out and disposal of excavated earth lead upto 50 m and lift upto 1.5 m, as directed by Engineer-in-charge. All kinds of soil.	60.00	cum		-	
4	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work up to plinth level :1:4:8 (1 Cement : 4 coarse sand (zone-III) derived from natural sources : 8 graded stone aggregate 40 mm nominal size derived from natural sources)	6.00	cum		-	
5	1:3:6 (1 Cement : 3 coarse sand (zone-III) derived from natural sources : 6 graded stone aggregate 20 mm nominal size derived from natural sources)	1.38	cum		-	
6	Providing and laying in position specified grade of reinforced cement concrete, excluding the cost of centering, shuttering, finishing and reinforcement - All work up to plinth level : 1:2:4 (1 cement : 2 coarse sand (zone-III) derived from natural sources : 4 graded stone aggregate 20 mm nominal size de rived from natural sources)	2.12	cum		-	
7	Centering and shuttering including strutting, propping etc. and removal of form for Lintels, beams, plinth beams, girders, bressumers and cantilevers	18.40	sqm		-	
8	Steel reinforcement for R.C.C. work ready to use "cut and bend" rebars of approved make from factory/workshop to construction site including placing in position and binding all complete upto plinth level. Thermo-Mechanically Treated bars of grade Fe-500D or more.	371.00	kg			
9	Random rubble masonry with hard stone in foundation and plinth including levelling up with cement concrete 1:6:12 (1 cement : 6 coarse sand : 12 graded stone aggregate 20 mm nominal size) upto plinth level with Cement mortar 1:6 (1 cement : 6 coarse sand) (Rubble Stone Material Shall be Provided by Department)	30.60	cum		-	

10	Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade: New work (Two or more coats applied @ 1.43 ltr/10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/10 sqm) Structural steel work riveted, bolted or welded in	193.00	sqm	-	
11	built up sections, trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete.	138.40	kg	-	
12	Demolishing stone rubble masonry manually/ by mechanical means including stacking of serviceable material and disposal of unserviceable material within 50 metres lead as per direction of Engineer-in-charge: In cement mortar	15.00	cum	-	
13	Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing: Providing and laying cement concrete in retaining walls, return walls, walls (any thickness) including attached pilasters, columns, piers, abutments, pillars, posts, struts, buttresses, string or lacing courses, parapets, coping, bed blocks, anchor blocks, plain window sills, fillets, sunken floor etc., up to floor five level, excluding the cost of centering, shuttering and finishing:	1.38	cum	-	
14	Suppy of RBT WIRE WITH BLADE PROFILE STRIP 0.40MM TO 0.45MM, WIRE DIA=2.50MM, PER COIL 100 MTR LENGTH APPROX	120.00	rmt	-	
15	Fixing of RBT Wire	120.00	rmt	-	
16	SUPPLY OF G I CONCERTINA COILS SIZE OF COIL: 450MM DIA GI COLD ROLLED CARBON STRIP THICKNESS: 0.40MM TO 0.45MM WIDTH OF TAPE: 12 MM APPROX, CORE WIRE: HIGH CARBON STEEL 2.50MM, SPIRALS 40 NOS. STRETCHABLE LENGTH: SMTRS LENGTH APPROX	40.00	rmt		
17	Fixing of G I CONCERTINA COILS	40.00	rmt	-	
18	Painting with synthetic enamel paint of approved brand and manufacture to give an even shade Two or more coats on new work	30.00	sqm	-	
<u> </u>	TOTAL (Inclus	sive of All Taxes)		0.00	